

Real-World Learning with Markov Logic Networks

Pedro Domingos

Dept. Computer Science & Eng.
University of Washington

(Joint work with Parag & Matt Richardson)



Overview

- Motivation
- Background
- Markov logic networks
- Inference in MLNs
- Learning MLNs
- Experiments
- Discussion




Motivation



- Machine learning / data mining systems must work with less help from people
- Automate data cleaning and integration
- Handle multiple types of objects and relations
- Easily incorporate domain knowledge

3

What's Needed



4



State of the Art

- **Learning:** Decision trees, SVMs, etc.
- **Logic:** Resolution, WalkSat, Prolog, description logics, etc.
- **Probability:** Bayes nets, Markov nets, etc.
- **Learning + Logic:** Inductive logic prog. (ILP)
- **Learning + Probability:** EM, K2, etc.
- **Logic + Probability:** Halpern, Bacchus, KBMC, PRISM, etc.

5



Learning + Logic + Probability

- Recent (last five years)
- Workshops: SRL ['00, '03, '04], MRDM ['02, '03, '04]
- Special issues: SIGKDD, Machine Learning
- All approaches so far use only **subsets** of first-order logic
 - Horn clauses (e.g., SLPs [Cussens, 2001; Muggleton, 2002])
 - Description logics (e.g., PRMs [Friedman et al., 1999])
 - Database queries (e.g., RMNs [Taskar et al., 2002])

6



Questions

- Is it possible to combine the full power of first-order logic and probabilistic graphical models in a single representation?
- Is it possible to reason and learn efficiently in such a representation?

7



Markov Logic Networks

- **Syntax:** First-order logic + Weights
- **Semantics:** Templates for Markov nets
- **Inference:** KBMC + MCMC
- **Learning:** ILP + Pseudo-likelihood
- **Special cases:** Collective classification, link prediction, link-based clustering, social networks, object identification, etc.

8




Overview

- Motivation
- Background
- Markov logic networks
- Inference in MLNs
- Learning MLNs
- Experiments
- Discussion

9

Markov Networks

- **Undirected** graphical models



- Potential functions defined over cliques

$$P(X) = \frac{1}{Z} \prod_c \Phi_c(X) \qquad Z = \sum_X \prod_c \Phi_c(X)$$

$$\Phi(A, B) = \begin{cases} 3.7 & \text{if } A \text{ and } B \\ 2.1 & \text{if } A \text{ and } \bar{B} \\ 0.7 & \text{otherwise} \end{cases}$$

$$\Phi(B, C, D) = \begin{cases} 2.3 & \text{if } B \text{ and } \bar{C} \text{ and } D \\ 5.1 & \text{otherwise} \end{cases}$$




10

Markov Networks



- **Undirected** graphical models



- Potential functions defined over cliques

$$P(X) = \frac{1}{Z} \exp\left(\sum w_i f_i(X)\right) \quad Z = \sum_x \exp\left(\sum_i w_i f_i(X)\right)$$

Weight of Feature i

Feature i

$$f(A, B) = \begin{cases} 1 & \text{if A and B} \\ 0 & \text{otherwise} \end{cases}$$

$$f(B, C, D) = \begin{cases} 1 & \text{if B and } \bar{C} \text{ and D} \\ 0 & \end{cases}$$

11

First-Order Logic



- Constants, variables, functions, predicates
E.g.: Anna, X, mother_of(X), friends(X, Y)
- Grounding: Replace all variables by constants
E.g.: friends (Anna, Bob)
- **World** (model, interpretation):
Assignment of truth values to all ground predicates

12

Example of First-Order KB



Smoking causes cancer

Friends either both smoke or both don't smoke

13

Example of First-Order KB



$\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

$\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$

14



Overview

- Motivation
- Background
- **Markov logic networks**
- Inference in MLNs
- Learning MLNs
- Experiments
- Discussion

15



Markov Logic Networks

- A logical KB is a set of **hard constraints** on the set of possible worlds
- Let's make them **soft constraints**:
When a world violates a formula,
It becomes less probable, not impossible
- Give each formula a **weight**
(Higher weight \Rightarrow Stronger constraint)

$$P(\textit{world}) \propto \exp\left(\sum \text{weights of formulas it satisfies}\right)$$

16



Definition

- A Markov Logic Network (MLN) is a set of pairs (F, w) where
 - F is a formula in first-order logic
 - w is a real number
- Together with a finite set of constants, it defines a Markov network with
 - One node for each grounding of each predicate in the MLN
 - One feature for each grounding of each formula F in the MLN, with the corresponding weight w


17

Example of an MLN

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$

Suppose we have two constants: **Anna** (A) and **Bob** (B)



18




Example of an MLN

$$1.5 \quad \forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$$

$$1.1 \quad \forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$$

Suppose we have two constants: **Anna** (A) and **Bob** (B)




19

Example of an MLN

$$1.5 \quad \forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$$

$$1.1 \quad \forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$$

Suppose we have two constants: **Anna** (A) and **Bob** (B)



20




Example of an MLN

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$

Suppose we have two constants: **Anna** (A) and **Bob** (B)



21

More on MLNs



- **Graph structure:** Arc between two nodes iff predicates appear together in some formula
- MLN is **template** for ground Markov nets
- **Typed** variables and constants greatly reduce size of ground Markov net
- Functions, existential quantifiers, etc.
- MLN without variables = Markov network (subsumes graphical models)

22



MLNs Subsume FOL

- Infinite weights \Rightarrow First-order logic
- Satisfiable KB, positive weights \Rightarrow Satisfying assignments = Modes of distribution
- MLNs allow contradictions between formulas
- How to break KB into formulas?
 - Adding probability increases degrees of freedom
 - Knowledge engineering decision
 - Default: Convert to clausal form

23



Overview

- Motivation
- Background
- Markov logic networks
- **Inference in MLNs**
- Learning MLNs
- Experiments
- Discussion

24

Inference



- Given query predicate(s) and evidence
 1. Extract minimal subset of ground Markov network required to answer query
 2. Apply probabilistic inference to this network
(Generalization of KBMC [Wellman et al., 1992])

25

Grounding the Template



- Initialize Markov net to contain all query preds
- For each node in network
 - Add node's Markov blanket to network
 - Remove any evidence nodes
- Repeat until done


26



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


27



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


28



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


29



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


30



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


31



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


32



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$


33



Example Grounding

1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$

1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$




$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$

34



Example Grounding

- 1.5 $\forall x \text{ Smokes}(x) \Rightarrow \text{Cancer}(x)$
- 1.1 $\forall x, y \text{ Friends}(x, y) \Rightarrow (\text{Smokes}(x) \Leftrightarrow \text{Smokes}(y))$



$$P(\text{Cancer}(B) \mid \text{Smokes}(A), \text{Friends}(A,B), \text{Friends}(B,A))$$

35



Probabilistic Inference

- Recall

$$P(X) = \frac{1}{Z} \exp\left(\sum_i w_i f_i(X)\right) \quad Z = \sum_X \exp\left(\sum_i w_i f_i(X)\right)$$

- Exact inference is #P-complete
- Conditioning on Markov blanket is easy:

$$P(x \mid MB(x)) = \frac{\exp\left(\sum_i w_i f_i(x)\right)}{\exp\left(\sum_i w_i f_i(x=0)\right) + \exp\left(\sum_i w_i f_i(x=1)\right)}$$

- Gibbs sampling exploits this

36

Markov Chain Monte Carlo



- **Gibbs Sampler**
 1. Start with an initial assignment to nodes
 2. One node at a time, sample node given others
 3. Repeat
 4. Use samples to compute $P(X)$
- Apply to ground network
- Many modes \Rightarrow Multiple chains
- Initialization: MaxWalkSat [Selman et al., 1996]

37

Overview



- Motivation
- Background
- Markov logic networks
- Inference in MLNs
- **Learning MLNs**
- Experiments
- Discussion

38



Learning

- Data is a relational database
- Closed world assumption
- Learning structure
 - Corresponds to feature induction in Markov nets
 - Learn / modify clauses
 - Inductive logic programming
(e.g., CLAUDIEN [De Raedt & Dehaspe, 1997])
- Learning parameters (weights)

39



Learning Weights

- Maximize likelihood (or posterior)
- Use gradient ascent

$$\frac{d}{dw_i} \log P(X) = f_i(X) - E_Y[f_i(Y)]$$

Feature count according to data

Feature count according to model

- Requires inference at each step (slow!)

40

Pseudo-Likelihood [Besag, 1975]



$$PL(X) \equiv \prod_x P(x \mid MB(x))$$

- Likelihood of each variable given its Markov blanket in the data
- Does not require inference at each step
- Very fast gradient ascent
- Widely used in spatial statistics, social networks, natural language processing

41

MLN Weight Learning



- Parameter tying over groundings of same clause
- Maximize pseudo-likelihood using conjugate gradient with line minimization

$$\nabla_i = \sum_x nsat_i(x) - [p(x=0)nsat_i(x=0) + p(x=1)nsat_i(x=1)]$$

where $nsat_i(x=v)$ is the number of satisfied groundings of clause i **in the training data** when x takes value v

- Most terms not affected by changes in weights
- After initial setup, each iteration takes $O(\# \text{ ground predicates} \times \# \text{ first-order clauses})$

42

Overview



- Motivation
- Background
- Markov logic networks
- Inference in MLNs
- Learning MLNs
- Experiments
- Discussion

43

Domain



- University of Washington CSE Dept.
- 24 first-order predicates:
Professor, Student, TaughtBy, AuthorOf, AdvisedBy, etc.
- 2707 constants divided into 11 types:
Person (400), Course (157), Paper (76), Quarter (14), etc.
- 8.2 million ground predicates
- 9834 ground predicates (tuples in database)

44



Systems Compared

- Hand-built knowledge base (KB)
- ILP: CLAUDIEN [De Raedt & Dehaspe, 1997]
- Markov logic networks (MLNs)
 - Using KB
 - Using CLAUDIEN
 - Using KB + CLAUDIEN
- Bayesian network learner [Heckerman et al., 1995]
- Naïve Bayes [Domingos & Pazzani, 1997]

45



Sample Clauses in KB

- Students are not professors
- Each student has only one advisor
- If a student is an author of a paper, so is her advisor
- Advanced students only TA courses taught by their advisors
- At most one author of a given paper is a professor

46



Methodology

- Data split into five areas:
AI, graphics, languages, systems, theory
- Leave-one-area-out testing
- Task: **Predict AdvisedBy(x, y)**
 - **All Info**: Given all other predicates
 - **Partial Info**: With Student(x) and Professor(x) missing
- Evaluation measures:
 - **Conditional log-likelihood**
(KB, CLAUDIEN: Run WalkSat 100x to get probabilities)
 - **Area under precision-recall curve**

47




Results


System	All Info		Partial Info	
	CLL	Area	CLL	Area
MLN(KB+CL)	-0.044	0.27	-0.040	0.25
MLN(KB)	-0.047	0.25	-0.043	0.20
MLN(CL)	-0.341	0.02	-0.852	0.03
KB	-0.124	0.16	-0.067	0.08
CL	-0.255	0.03	-0.371	0.04
NB	-0.218	0.17	-0.059	0.19
BN	-0.095	0.02	-0.166	0.04

48

Results: All Info



Results: Partial Info



Efficiency



- Learning time: 88 mins
- Time to infer all 4900 AdvisedBy predicates:
 - With complete info: 23 mins
 - With partial info: 24 mins

51

Overview



- Motivation
- Background
- Markov logic networks
- Inference in MLNs
- Learning MLNs
- Experiments
- Discussion

52



Related Work

- Knowledge-based model construction
[Wellman et al., 1992; etc.]
- Stochastic logic programs
[Muggleton, 1996; Cussens, 1999; etc.]
- Probabilistic relational models
[Friedman et al., 1999; etc.]
- Relational Markov networks
[Taskar et al., 2002]
- Etc.

53



Special Cases of Markov Logic

- Collective classification
- Link prediction
- Link-based clustering
- Social network models
- Object identification
- Etc.

54



Future Work: Inference

- Lifted inference
- Better MCMC (e.g., Swendsen-Wang)
- Belief propagation
- Selective grounding
- Abstraction, summarization, multi-scale
- Special cases

55



Future Work: Learning

- Faster optimization
- Beyond pseudo-likelihood
- Discriminative training
- Learning and refining structure
- Learning by reformulation

56



Future Work: Applications

- Object identification
- Information extraction & integration
- Semantic Web
- Social networks
- Assisted cognition
- Using world knowledge in parsing
- Using world knowledge in scene analysis
- Etc.

57



Conclusion

- Machine learning / data mining systems must work with less help from people
- **Markov logic networks** combine first-order logic and prob. graphical models
 - **Syntax:** First-order logic + Weights
 - **Semantics:** Templates for Markov networks
- **Inference:** MCMC over minimal grounding
- **Learning:** Pseudo-likelihood and ILP
- Experiments on UW DB show promise

58